

Platinum HD-TVI Covert Camera CM1924T



Key Features:

- Full HD 1080P
- 1/2.8" Sensor
- 3.7mm Lens
- Support UTC Function
- Support 2D/3D NR
- DC 12V

Dimensions:








1080P









Platinum HD-TVI Covert Camera CM1924T

| CAMERA | |
|-------------------------|---|
| Image Sensor | 1/2.8" CMOS |
| Signal System | NTSC/PAL |
| Effective Pixels | 1944(H)*1213(V) |
| Min. Illumination | 0.1 Lux |
| Shutter Speed | 1/30(1/ 25)s to 1/50,000 s |
| Lens | 3.7mm Lens |
| Synchronization | Internal |
| Video Frame Rate | 1080p@30fps/1080p@25fps |
| Digital Noise Reduction | 2D NR & 3D NR |
| S/N Ratio | More than 50dB |
| GENERAL | |
| Working Temperature | 14 ° F - 122 ° F (-10 ° C - 50 ° C) |
| /Humidity | Humidity 90% or less (non-condensing) |
| Power Supply | DC 12V |
| Power Consumption | Max. 3W |
| Dimension | 4.7″ x 2.0″ x2.2″ (120mm x 59mm x 57mm) |
| Weight | 0.4lb(200g) |

©2015 LT Security, Inc. All Rights Reserved. White papers, data sheets, quick start guides, and/or user manuals are for reference only and may or may not be entirely up to date or accurate based upon the version or models. Product names mentioned herein may be the unregistered and/or registered trademarks of their respective owners.