


## **HD-TVI Turret Camera** CMHT2722-28




## **Key Features:**

- HD 1080P Video Output
- Adopt HDTVI Technology
- True Day/Night
- Smart IR
- 131ft(40m) IR distance
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

## **Dimensions:**




































## HD-TVI Turret Camera CMHT2722-28

| CAMERA                |  |
|-----------------------|--|
| Image Sensor          | 1/2.9" CMOS                                      |
| Signal System         | NTSC/PAL   |
| Effective Pixels      | 1930(H)*1088(V)                                  |
| Min. Illumination     | 0.01 Lux, 0 Lux with IR                          |
| Shutter Speed         | 1/30(1/25) s to 1/50,000 s                       |
| Lens                  | 2.8mm  |
|                       | Angle of View: 105.8°                            |
| Day & Night           | ICR  |
| Synchronization       | Internal   |
| Video Frame Rate      | 1080p@30fps/1080p@25fps                          |
| HD Video Output       | 1 Analog HD Output                               |
| S/N Ratio             | More than 52dB                                   |
| MENU                  |  |
| AGC                   | Support  |
| D/N Mode              | Color/ BW/ Smart                                 |
| White Balance         | ATW/MWB  |
| Language              | English  |
| Function              | Digital noise reduction, Mirror                  |
| GENERAL               |  |
| Working Temperature   | -40 ° F - 140 ° F (-40 ° C - 60 ° C)             |
| /Humidity             | Humidity 90% or less (non-condensing)            |
| Power Supply          | DC 12V   |
| Power Consumption     | Max. 3.5W  |
| Weather Proof Ratings | IP66   |
| IR Range              | Up to 131ft(40m)                                 |
| Dimension             | $\varphi$ 5.0" × 4.0"( $\varphi$ 126.7× 102.1mm) |
| Weight                | 1.1lb(500g)                                      |