



Full GUI with alpha blending • Individual setting of resolution • frame rates and picture quality • Instant Replay • Digital Zoom • Mouse Control • Weekly scheduler with holiday by 10 minutes setting • Covert • Disable and Private function of cameras • Motion Detection with 576 area setting • Relay alarm output • PTZ control by RS-485 • Daylight Saving Time and Network Time Setting • Multi User Authority • Deinterlacer upon live and playback • Multi languages with full graphic • Individual Network port setting • Auto Deletion • Import and Export the configuration • Interactive setup via network • POS Interface • Mirroring

UVST-MAGIC-4K16 1/6



What is Magic Technology?

Magic Technology is designed to adopt various video signal types in a single Digital Video Recorder. In other words, any past generation analog CCTV cameras you own, as well as the newest technilogy, EX-SDI, digital CCTV-cameras will work seamlessly with the Magic DVR. Magic technology bridges the gap between analog security and the next generation high definition digital security.


What is EX-SDI?



UVST-MAGIC-4K16 2/6

The Secrets

EX-SDI utilize low frequency signal combine with the new VLC (Visually Lossless CODEC) technology, able to push up 99% identical image quality at more than twice the transmission distance.



Ready for 4K

EX-SDI is built in mind of adopting 4K resolution to security. Thanks to the EX-SDI VLC feature, because of that it is possible to transmit 4K in realtime FPS over coaxial cable.

Backward Compatibility

EX-SDI Magic series will work with any HD-SDI cameras. Just like the Magic series once were compatible with their predecessors' technologies

Video Balun compatible

UTP cable is another option to transmit EX-SDI video signal in order to reduce cable cost. Specialized video balun for EX-SDI is required. (sold separately)

UVST-MAGIC-4K16 3/6



SPECIFICATIONS

Video		
Camera input	16 BNC	
Individual HD/Analog selectable	Analog, HD-SDI, EX-SDI, TVI, AHD, CVI, IP	
Available source	Upto 8MP IPC EX-SDI 720p25,30/1080p25,30/4MP 25,30/8MP 25,30 TVI/AHD/CVI 720p25,30/1080p25,30/3MP 18/4MP@12 ~ 30 HD-SDI 720p25,30/1080p25,30 /Composite/960H/Mixed	
IP Camera Spec	ONVIF 2.3, RTSP, H.264, dual stream use gigabit ethnet hub	
IP Camera Num	8	
IP Camera Restriction	Cannot setup Private ZONE Cannot support Timestamp	
Output	2 HDMI (Main Display or Programmable HD Spot) 1 VGA (Main Display or Programmable HD Spot) 1 Composite (Programmable SPOT)	
Audio		
Audio input	16 RCA	
Output	1 RCA	
Sensor In	16 (NC, NO selectable)	

UVST-MAGIC-4K16 4/6

Magic U 4K Series | 16CH Octa-brid DVR System, All-channel 4K Recording, 8 HDD slots, eSATA, 16CH Audio

Alarm out	2 Relay, 14 TTL	
Operating System	Embedded Linux OS	
Display		
Speed	Real Time	
Resolution (Pixel)	1280 × 1024, 1280 × 720, 1920 × 1080, UHD	
Split screen	1,4,6,8,9,13,16	
Main Recording		
CODEC	H.264	
Resolution (Pixel), Video IN : Possible Recording	8MP: 8MP, 1080p 4MP: 4MP, 720p 3MP: 3MP, 720p 1080p: 1080p, 720p 720p: 720p, 960 × 540 960H, Composite: 960H, D1	
Picture quality	4 steps (Super, High, Medium, Low)	
Speed	240fps @ 8MP	
Dual Recording		
CODEC	H.264	
Resolution (Pixel)	640 × 360	
Playback		
Display	1,4,6,8,9,13,16	
Search mode	Calendar, Event ,POS , Panorama, Thumbnail	
Speed	480 fps	
Fast/Slow speed	Normal, REW & FF [recorded speed \times 2, \times 4, \times 8, \times 16,x32,x64,x1/2,x1/4], Frame to frame, Pause	
Network (Individual setting of resolution, frame rates and picture quality)		
Network Interface	Gigabit Ethernet	
High Resolution (Pixel) Video IN : Possible Recording	8MP: 1080p, 720p 4MP: 1080p, 720p 3MP: 1080p, 720p 1080p: 1080p, 720p 720p: 720p, 960 × 540 960H, Composite: 960H, D1	

UVST-MAGIC-4K16 5/6

Magic U 4K Series | 16CH Octa-brid DVR System, All-channel 4K Recording, 8 HDD slots, eSATA, 16CH Audio

Low Resolution (Pixel) Video IN : Possible Recording	8MP: 480 × 256 4MP: 480 × 256 3MP: 480 × 256 1080p: 480 × 256 720p: 480 × 256 960H, Composite: CIF	
Speed	140fps @ 1080p	
Protocol	TCP/IP, HTTP, DHCP	
Application	Windows 7 / 8 (PC Client system& IE)/MAC	
Web Browser	Internet Explorer, Safari, Chrome, Firefox	
Smart phone App	Android, iPhone for live and search	
Backup		
Interface	USB 2.0 × 3	
Backup device	External HDD and CD/DVD-RW, Network, Thumb Drive	
The number of HDD	8 SATA + 1 eSATA(upto 8 bays, No capacity limit; 8TB or more)	
Others		
Power Consumption	150W	
Operating Temperature	41°F ~ 104°F(5°C ~ 104°C)	
Relative Humidity	Maximum 80% non-condensing	
Dimension	17(W) × 16.6(D) × 3.47(H)in	

UVST-MAGIC-4K16 6/6