

# EX-SDI 4MP Outdoor IR Bullet Camera with Fixed Lens, IP68, 25 IR LED, DC 12V



1/2.9 inch SONY CMOS (IMX-326) / Upgraded Waterproof Housing • High Definition Serial Digital Interface / 0 Lux at IR On (IR 25) • WDR (Wide Dynamic Range) / DNR (Digital Noise Reduction) / Day & Night • Fixed Length : 3.6 mm

## SPECIFICATIONS

|                  |                                   |
|------------------|-----------------------------------|
| Resolution       | 1440P, 1080P, 720P                |
| Sensor           | 1/2.9 inch SONY CMOS (IMX-326)    |
| Total Pixels     | 3096(H) × 2218(V) = 6.87M         |
| Scanning System  | PROGRESSIVE                       |
| S/N (Y signal)   | More than 52 dB (AGC Off)         |
| Video Output     | SMPTE274M (EX-SDI, HD-SDI)        |
| Min.Illumination | 0 Lux at IR On                    |
| White Balance    | AUTO / AUTO EXT / PRESET / MANUAL |

# EX-SDI 4MP Outdoor IR Bullet Camera with Fixed Lens, IP68, 25 IR LED, DC 12V

|                          |  |
|--------------------------|--|
| Electronic shutter speed | AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER  |
| Brightness               | ADJUSTABLE (0 ~ 20 STEP)   |
| DNR                      | OFF / LOW / MIDDLE / HIGH  |
| BACKLIGHT                | OFF / WDR / BLC / HLC  |
| Day & Night              | AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN  |
| PRIVACY / MOTION         | OFF / ON   |
| Language                 | ENG, CHN, CHN(S), JPN, KOR   |
| Sharpness                | ADJUSTABLE (0 ~ 10 STEP)   |
| COMM.                    | RS-485(PELCO-D)  |
| Temperature/Humidity     | Operating (14°F ~ 122°F(-10°C ~ 50°C)/ 30% ~ 80% RH) / Storage (-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH)                           |
| Power                    | DC12V  |
| signal Transmission      | The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI 100M / EX-SDI 500M) |