

# 1080P EX-SDI / HD-SDI Hidden Square Case Camera with Fixed Lens, DC 12V



1/2.9" SONY CMOS • Extended Serial Digital Interface • 1 Lux @F1.2, 0.1 Lux (B/W) • DNR(Digital Noise Reduction) • Day & Night(ICR Option) • Easy Installation

## SPECIFICATIONS

|            |   |
|------------|---|
| Resolution | 1080P                                     |
| Sensor     | 1/2.9 inch SONY CMOS (IMX-222 / IM x 322) |

# 1080P EX-SDI / HD-SDI Hidden Square Case Camera with Fixed Lens, DC 12V

|                          |  |
|--------------------------|--|
| Total Pixels             | 2000(H) × 1241(V) = 2,482,000  |
| Effective Pixels         | 1944(H) × 1092(V) = 2,122,648  |
| Scanning System          | PROGRESSIVE  |
| S/N (Y signal)           | More than 52 dB (AGC Off)  |
| Video Output             | SMPTE292M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)  |
| Min.Illumination         | 1 Lux at F1.2 / 0.1 Lux (B/W)  |
| White Balance            | AUTO   |
| Electronic shutter speed | AUTO   |
| DNR                      | ON   |
| Day & Night              | AUTO (Day <--> Night TIME Change)  |
| Temperature/Humidity     | Operating (14°F ~ 158°F(-10°C ~ 70°C) / 30% ~ 80% RH) / Storage (14°F ~ 104°F(-10°C ~ 40°C) / 20% ~ 90% RH)                              |
| Power                    | Only DC12V   |
| signal Transmission      | The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (400M)) |