

Anti-IR Reflection | 2MP EX-SDI STORM® IR IP68 andal-Resistant Dome Camera with Vari-Focal Lens, True WDR, L-size, AC 24V/DC 12V Duel Power



1/2.8 inch SONY CMOS (IMX-290) / HD-SDI (1080P, 720P) • 0 Lux at IR On (IR LED 4 pcs) / Upgraded Waterproof Housing (IP 68 rating) • DNR (Digital Noise Reduction) / HIGH DEFINITION SERIAL DIGITAL INTERFACE/ • WDR (Wide Dynamic Range) /Day & Night (ICR Option) / Easy Installation • ICR V/F lens, DC Auto IRIS V/F Lens, DC Auto IRIS & TDN V/F Lens • Focal Length : 2.8~12mm • 1group

What is EX-SDI?

Union of great advantages from all existing technologies

HD-SDI

- Digital lossless quality
- Strong resistance to interference

HD-TVI • CVI • AHD


- Long transmission distance
- Able to use video baluns

EX-SDI
THE NEXT GENERATION HD-TECHNOLOGY

Anti-IR Reflection | 2MP EX-SDI STORM® IR IP68 andal-Resistant Dome Camera with Vari-Focal Lens, True WDR, L-size, AC 24V/DC 12V Duel Power

The Secrets

EX-SDI utilize low frequency signal combine with the new VLC (Visually Lossless CODEC) technology, able to push up 99% identical image quality at more than twice the transmission distance.



Ready for 4K

EX-SDI is built in mind of adopting 4K resolution to security. Thanks to the EX-SDI VLC feature, because of that it is possible to transmit 4K in realtime FPS over coaxial cable.

Backward Compatibility

EX-SDI Magic series will work with any HD-SDI cameras. Just like the Magic series once were compatible with their predecessors' technologies

Video Balun compatible

UTP cable is another option to transmit EX-SDI video signal in order to reduce cable cost. Specialized video balun for EX-SDI is required. (sold separately)

Anti-IR Reflection | 2MP EX-SDI STORM® IR IP68 andal-Resistant Dome Camera with Vari-Focal Lens, True WDR, L-size, AC 24V/DC 12V Duel Power



SPECIFICATIONS

Resolution	1080P, 720P
Sensor	1/2.8 inch SONY CMOS (IMX-290)
Total Pixels	1945(H) × 1109(V) = 2.16M
Effective Pixels	1945(H) × 1097(V) = 2.13M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE274M (EX-SDI, HD-SDI) / (CVBS : 1.0Vp-p (75ohm))
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Shutter	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
Brightness	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF / × 2 ~ × 32
DNR / ACE	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / MOTION / FLIP / DEFOG	OFF / ON

Anti-IR Reflection | 2MP EX-SDI STORM® IR IP68 andal-Resistant Dome Camera with Vari-Focal Lens, True WDR, L-size, AC 24V/DC 12V Duel Power

Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485(PELCO-D)
Smart IR	ADJUSTABLE (0 ~ 20 STEP)
Temperature/Humidity	Operating (14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH) / Storage (-4°F ~ 140°F(-20°C ~ 60°C)/ 20% ~ 90% RH)
Power	AC24V / DC12V DualPower
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI 100M / EX-SDI 500M)