

CERTAINTY 400 SERIES NETWORK VIDEO RECORDER

ENTERPRISE COMMERCIAL VIDEO STORAGE APPLIANCE



experience to accommodate our partners from planning and deployment to monitoring and post-sale support.

The Seneca Certainty 400 Series NVR is purpose-built with one thing in mind: highcamera-count, large-retention video surveillance installations. From transportation to government facilities - and any venue in between - the Seneca Certainty 400 series is the server of choice.

THE SENECA DIFFERENCE



Seneca's exclusive xConnect platform puts you in complete control of your security hardware with an easy-to-use dashboard that allows you to audit, manage and act remotely. Instant alerts report problems before customers do, making you more proactive. Off-site control means less truck rolls and more profitability.



Also standard with all Seneca NVRs, maestro gets your optimized system up and running in minutes instead of hours. We channeled years of value engineering into an intuitive dashboard that eliminates hundreds of keystrokes. You don't even need an internet connection or data transfer from external drives.

KEY FEATURES

- Comes standard with xConnect and Experience Launcher technology
- Five-year global next-day, on-site service warranty
- Up to 216 TB of raw storage retention
- RAID options 0, 1, 5, 6, 10
- Tested, validated and certified with top VMS applications
- Performance tunings optimized for specific VMS
- Provides 400-600 Mbps recording rate performance optimized for specific VMS



:Seneca

CERTAINTY 400 SERIES NETWORK VIDEO RECORDER

SPECIFICATIONS

SYSTEM

Processor	2 x Intel® Xeon® Silver Processor Family		
Operating System	Windows Server 2016; Windows 10 IoT		
Manufacturer	Seneca		
Memory	Default: 64 GB (8 x 8GB) DDR4 2666MHz ECC configured in Quad-Channel Mode Option: 96 GB (12 x 8GB) DDR4 2666MHz ECC configured in Six-Channel Mode		
Maximum Data Storage	Up to 216TB RAW in a Single Chassis		
Video Outputs	VGA Optional NVIDIA Quadro P1000 GPU Optional NVIDIA Quadro P2000 GPU		
Graphics	Onboard graphics		
Networking	4 x 1GbE (optional + 2 x 10GbE SFP+ Configuration)		
USB	Front: 2 x USB 2.0; Rear: 2 x USB 3.0		
Expansion Slots	H840 Storage Expander; Connect up to 4 JBOD Expansion Chassis @ 96TB each		
RAID	Operating System RAID: 2 x 240GB SSD (RAID 1) Data RAID Level: PERC H740P JBOD, 0, 1, 5, 6, 10		
High Speed Live Drive	2, 4, 6 or 8 x 1.2TB 10K SAS Option		
NVR Hardware Monitoring	Pre-Installed with Seneca xConnect Server Agent; IDRAC 9 Express		
Warranty	5 Year Global Next Day, Onsite Warranty Standard		

MECHANICAL

Form Factor	2U Rackmount	
OS Drive Bays	2 x M.2 BOSS PCle Card	
Data Drive Bays	Up to 18 x 3.5" Hot Swappable	
Power Supply	1+1750W hot plug redundant 80+ Platinum	
Ambient Operating Temp	10°C to 35°C (50°F to 95°F)	
Operating Humidity	5% ~ 90% non-condensing	
Dimensions (w x h x d)	17.08 x 3.4 x 28.16 in / 434 x 86 x 715 mm	
Weight	71.5 lbs / 32.5 kg fully populated	



