

ATLAS SERIES



SF1005V

Face Recognition for high-speed applications

- Enhanced visible light facial recognition with 6,000 face templates capacity deep learning built-in
- facial recognition
- 5-inch touch I CD

FEATURES

- Dual-camera for real-time face detection
- Recognition distance: 0.3 3 m
- Multiple verification with fingerprint, RFID and Compatable with external RS232, RS485, and Wiegand reader
 - TCP / IP, WiFi communication

Recognition distance up to 3m long and extra wide angle recognition

The recognition distance has been greatly extended up to 3 meters +/-30 Degrees long, which significantly improves maximum trafic rate. While most of algorithms only support 15-degree angle facial recognition, ZKTeco supports 30-degree angle facial recognition. +/- 30 Degrees +/-30 Degrees +/- 30 Degrees 3 meters distance +/- 30 Degrees

SPECIFICATIONS

Model SF1005V

LCD |5in touch screen

CPU Quad-core A17 1.8GHz
Memory 2G RAM/ 16G ROM

Camera | 2MP dual lens, TCP/IP, WiFi, (optional)

Communication | RS232, RS485 for external reader,

Wiegand input/output

Accessory Door lock, door snsor, alarm, exit

button, & auxilary input

Audio | Loudspeaker

Users | 10,000

Face Template 6,000

Fingerprint | 10,000 (optional) | RFID | 10,000 (optional)

Log 200,000

Voltage 12V 3A

Temperature Humidity 14°F - 113°F 10% - 90%

Software | ZKBioAccess

OPTIONAL ACCESSORIES



RS485 Fingerprint Reader



RFID Reader



Exit Button




Electric Lock



Alarm



Sensor



DIMENSIONS (IN)





1600 Union Hill Rd., Alpharetta GA 3000**5**

Phone: (862) 505 - 2101 • Fax: (862) 204 - 5906 • sales@zktecousa.com • www.zktecousa.com