

# LTN8704-P4/8708-P8/8716-P8

## Embedded Plug & Play NVR



LTN8704-P4




LTN8708-P8/LTN8716-P8

### Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920 × 1080P resolution
- 4/8/16-ch network cameras can be connected with 25M/50M/100M incoming bandwidth
- Up to 2 SATA interfaces
- Plug & Play with up to 8 independent PoE network interfaces
- Support network detection, including network delay packet loss, etc,

### RearPanel of LTN8704-P4/LTN8708-P8



LTN8704-P4



LTN8708-P8/LTN8716-P8

1. PowerSupply
2. Audio In
3. HDMI Interface
4. LANNetwork Interface
5. Audio Out
6. VGA Interface
7. USB Interface
8. Ground
9. PowerSwitch
10. Network InterfaceswithPoEFunction

	LTN8704-P4	LTN8708-P8	LTN8716-P8
<b>Video/Audio input</b>			
IP video input	4-ch	8-ch	16-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)		
<b>Network</b>			
Incoming bandwidth	25Mbps	50Mbps	100Mbps
Outgoing bandwidth	80Mbps		
Remote connection	128		
<b>Video/Audio output</b>			
Recording resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
Frame rate	Main stream: 50 fps (P) / 60 fps (N)		
	Sub-stream: 50 fps (P) / 60 fps (N)		
HDMI/VGA output	1-ch, resolution:1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
Audio output	1-ch, RCA (Linear, 1kΩ)		
<b>Decoding</b>			
Live view / Playback resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
Capability	4-ch@1080P	8-ch@720P, 6-ch@1080P	16-ch@4CIF, 12-ch@720P, 6-ch@1080P
<b>Hard disk</b>			
SATA	1 SATA interface for 1 HDD	2 SATA interface for 2 HDDs	
Capacity	Up to 4TB for each disk		
<b>External interface</b>			
Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface		
USB interface	1 × USB 2.0 and 1 × USB 3.0		
<b>PoE</b>			
Interface	4 independent 100 Mbps PoE network interfaces	8 independent 100 Mbps PoE network interfaces	
Max. Power	50W	120W	
Supported standard	AF and AT		
<b>Others</b>			
Power supply	48V DC	100~240V AC	
Consumption (without hard disk)	≤ 10W		
Working temperature	14° F~131° F(-10° C ~ +55° C)		
Working humidity	10% ~ 90%		
Chassis	1U chassis	19-inch rack-mounted 1U chassis	
Dimensions(W × D × H)	315 × 230 × 45mm (12.4 × 9.1 × 1.8 inch)	445 × 290 × 45mm (17.5 × 11.4 × 1.8 inch)	
Weight(without hard disk)	≤ 1 Kg (2.2 lb)		