



FULL HD OVER COAX USE YOUR EXISTING COAX CABLE

HDSDI

x30 OPTICAL ZOOM

1080P PTZ SPEED DOME CAMERA



FEATURES

- ▶ 2.0 Mega-Pixel Resolution PTZ
- ▶ HD-SDI 1080p output @25/30fps
- ▶ 4.3~129mm Vari-focal Mega-pixel Lens
- ▶ Service analog video output
- ▶ Vector Drive and Micro-Stepping Technology make more smooth rotation and accurate preset
- ▶ Compound Movement make the speed dome reach preset in shortest route
- ▶ True Day & Night with ICR (IR Cut Filter)
- ▶ WDR (Wide Dynamic Range)
- ▶ DNR (Digital Noise Reduction)
- ▶ DSS (Digital Slow Shutter) enhance sensitivity in night time
- ▶ HLC (High Light Compensation)
- ▶ Defog to clear dome cover by hot air
- ▶ 360° endless horizontal rotation
- ▶ 90° vertical movement, 180° vertical movement
- ▶ Max. 400°/sec. Preset speed
- ▶ 254 presets, 8 auto scan
- ▶ 4 pattern, 8 groups could be programmed
- ▶ 16 schedule could be programmed by month, week, day
- ▶ Auto focus, auto flip, power up action
- ▶ Zoom proportional could be selected
- ▶ Powerful park function
- ▶ 8 privacy zone could be programmed
- ▶ IP66 Outdoor
- ▶ Adequate protection against lightening strikes and power surges
- ▶ DC12V/AC12V Dual-voltage power supply
- ▶ Provide extra DC12V 500mA service power supply for other device (Outdoor)

Image Sensor	1/2.86" Panasonic CMOS Sensor
Video Output	1080p @25/30fps
Zoom	30× optical zoom / 32× digital zoom
Focal Length	F1.6(wide)~5.0(tele); f=4.3~129mm
Minimum Illumination	Color:0.5Lux, BW:0.1Lux; Color DSS:0.002Lux, BW DSS:0.001Lux
Day & Night	Active/Passive/Day/Night/Schedule
Focus	Auto/Manual/Semi-auto
Iris	0--20
Shutter Speed	1/30(25)--1/60000sec.
AGC	Off/On
White Balance	Auto
Mirror	None/Horizontal/Vertical/Horizontal & Vertical
WDR	High/Low/Disable
Privacy Zone	8 privacy zone could be programmable
DNR	Off / Low / Middle / High
Defog	On/Off
HLC	On/Off
BLC	On/Off
Flickerless	On/Off
Brightness	Adjustable (0-20)
Pan/Tilt Range	Horizontal: 360°(Endless)/Vertical: 90°
Speed	Preset : 400° / sec. Manual : 0 ~ 360° / sec. (proportional to zoom ratio)
Preset	254
Auto Scan	8
Pattern	4
Group	8
Schedule	16
Other functions	Auto Flip, Park Position, Power Up
Communication	RS-485
Protocol	Pelco-D, Pelco-P
Alarm I/O	8/4 I/O Alarm
Input Voltage	DC 12V/ AC 24V
Max. Power Consumption	DC12V: Max.26W; AC24V: Max.65W
Dimensions	Ø230mmx325Hmm
Weight	Indoor:1.9KG(with ceiling bracket); Outdoor3.1KG (w/o bracket)
Working Temperature	-42° to 55°
Fan/Heater Temp.	(Outdoor) Fan start temp.: Start temp.: 45° and 0°; Heater: 0°
Working Humidity	0%~90% (Non-condensation)