

# HDSDI<sup>CE</sup> 1080P IR DOME CAMERA



- 2.8~12mm Mega-pixel Lens
- True Day & Night (ICR)
- DC 12V



## ANTI-IR REFLECTION SERIES

PREVENTS WASHED OUT VIDEO CAUSED BY IR REFLECTION FROM OBSTACLES (WATER OR OIL) ON COVER

## 4 PCS OF HIGH POWERED IR


SEE MUCH DETAILS IN A GREAT DISTANCE

## SMART IR

PREVENTS WASHED OUT IMAGE CAUSED BY INTENSE IR LIGHT AT A CLOSE RANGE

ANTI-IR REFLECTION CAMERA

COMPETITOR'S DOME CAMERA



- HD-SDI : The Next Generation HD Security. 1080p FULL HD Flawless Video
- **Anti-IR Reflection Series** : (The Shield) : Prevents washed out video caused by IR reflection from obstacles (water or oil) on cover (U.S. Patent Pending)
- **4 High Powered IR LED** : Up to 50% more brighter than conventional IR LED
- **Easy Twist and Lock Installation** : No drilling thru camera required (Drill hole guide included)
- **4-Axis Construction** : By adjusting '4-Axis' control, you get a straight view regardless whether the camera is installed on a wall or ceiling
- **Dual Video Output** (HD-SDI / CVBS)
- 1/2.9 inch Sony CMOS : Low Power Consumption
- Minimum Illumination - 0 Lux with IR on
- 2.8~12mm Auto-Iris **IR Corrected** Lens Installed - provides the best focused image both color & IR mode
- Auto Removable IR-Cut Filter (ICR) : True Day & Night. Deep color and clear video at both day and night time
- OSD (On Screen Display) - Easy Camera Setup
- DNR (Digital Noise Reduction), D-WDR (Digital Wide Dynamic Range), HLM (High Light Masking), MDIR (Motion Detection IR) and more advanced image enhancing features

Resolution	HD-SDI (1080p, 720p) / over 1000 TV Line
Sensor	1/2.9 inch Sony CMOS
Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	Progressive
S/N (Y Signal)	More than 52 dB (AGC Off)
Video Output	SMPT292M (HD-SDI) CVBS: 1.0Vp-p (750hm)
Min. Illumination	0 Lux at IR On
White Balance	Auto / Auto Ext / Preset / Manual
Shutter	Auto / Manual (1/30sec ~ 1/60,000sec)
Brightness	Adjustable (0~20 Step)
Sens Up	Off / ×2~8
DNR	Off / Low / Middle / High
WDR / BLC	Off / WDR / BLC
HLM	Off / Set
ACE	Off / Low / Middle / High
Day & Night	Auto ( Day <-> Night time change) Color , B/W, Extern, MDIR
Privacy	Off / On (16 Zone)
Motion	Off / Set
Digital Zoom	up to ×127
Flip	Off / On
Freeze	Off / On
Language	English
Sharpness	Adjustable (0~10 Step)
Defog	Off / Set
Communication Port	RS-485 ( PELCO-D )
Smart IR	Adjustable (0~20 Step)
Operating Temp / Humidity	-10°C ~ +50°C (14°F ~ 122°F) / 30%~80% RH
Storage Temp / Humidity	-20°C ~ +60°C (-4°F ~ 140°F) / 20%~90% RH
Power	DC 12V
Dimensions	5.79"(Ø) x 5.38"(H) / 147mm(Ø) x 136.74mm(H)