

IT JUST WORKS! This technology bridges the gap between analog security and the next generation high definition digital security

and the next generation high definition digital security.

WHAT IS THIS TECHNOLOGY?

This Technology is designed to adopt various video signal types in a single Digital Video Recorder. In other words, any past generation analog CCTV cameras you own, high definition digital CCTV- cameras will work seamlessly with the DVR.

- Automatically Detects Analog / 960H / HD-TVI Camera
- H.264 High Compression CODEC
- Programmable Spot Out
- iPhone® Android® Remote View App Availat
- Crystal Clear 1080p Live Video Quality

- POS Interface Ready
- RS-485 for PTZ Control
- Free DDNS Support

REAR PANEL





HDD INSTALLATION AVAILABLE UPON REQUEST IR REMOTE & MOUSE INCLUDED

1. Cellular data service required. Software may not compatible due to OS version requirement





HOW IT WORKS

 $\langle \boldsymbol{a} \rangle$

Upgrade just can't get any easier than this, just unplug all cameras from the old DVR and plug them back into the new DVR, it will just work. Absolutely no training or knowledge is necessary.

The best feature about the DVR is that both analog and HD-TVI cameras work in a single DVR. FULL HD security is not a luxury option any more, it is a must for today's security.



- Full Gui With Alpha Blending
- Individual Setting Of Resolution, Frame Rates And Picture Quality
- **Instant Replay**
- Digital Zoom (Live & Playback)
- Mouse Control
 Weekly Scheduler With Holiday By 10 Minutes Setting
- Covert, Disable And Private Function Of Cameras
- Motion Detection With 352 Area Settings
- Relay Alarm Output
- PTZ Control By RS-485
- Daylight Saving Time And Network Time Setting
 Multi-User Authority Up To 8 Users
- De-Interlacer Upon Live And Playback
- 22 Languages With Full Graphic
- Individual Network Port Setting
- Auto Deletion
- Import And Export The Configuration
- Mirroring
- POS Interface
- Dual Codec Engine For Independent Video Transmission
- Interactive Setup via Network

ACCESSORIES



HDD INSTALLATION AVAILABLE UPON REQUEST **IR REMOTE & MOUSE INCLUDED**

SMART PHONE COMPATIBLE	
MR. Patrol	

Visiting Analog Visiting Analog			
Video	Camera Input	16 BNC	
	Individual HD/Analog	All Hybrid	
	Available Source	TVI 720p25,30/1080p25,30/Composite/960H/Mixed	
	Output	1 HDMI (Main Display or Programmable HD Spot) 1 VGA (Main Display or Programmable HD Spot) 1 Composite (Programmable SPOT)	
Audio	Audio Input	4 RCA	
	Output	1 RCA	
Sensor In		4 (NC, NO selectable)	
Alarm out		1 Relay	
Operating System		Embedded Linux OS	
Display	Speed	Real Time	
	Resolution (Pixel)	1280×1024, 1280×720, 1920×1080	
	Screen Split	1/4/6/8/9/13/16	
Recording	CODEC	H.264 / JPEG for 3G, Dual CODEC	
	Resolution (Pixel)	1080p (1080p25,30) 720p (720p25,30) 960H, 720H (Composite, 960H)	
	Picture Quality	4 Steps (Super, High, Medium, Low)	
	Speed	NTSC : 480fps@720p / 240fps@1080p PAL : 400fps@720p / 200fps@1080p	
Playback	Display	1/4/8/9/13/16	
	Search Mode	Calendar, Event ,POS , Panorama, Thumbnail	
	Speed	NTSC: 120fps@1080p PAL: 100fps@1080p	
	Fast/Slow speed	Normal, REW & FF [recorded speed ×2, ×4, ×8,×16,×32,×64,×1/2,×1/4], Frame to frame, Pause	
Network	Network Interface	Gigabit Ethernet	
	Speed	100fps@720p	
	Protocol	TCP/IP, HTTP, DHCP	
	Application	Windows 7 / 8 (PC Client system & IE)/MAC	
	Web Browser	Internet Explorer, Safari, FireFox, Chrome	
Bookur	Smart phone App	MR. Patrol : Android, iPhone for Live & Search	
Backup	Interface Rackup dovice	USB 2.0 × 2 External HDD, CD & DVD BW/ Notwork, Thumb Drive	
Backup device		External HDD, CD & DVD-RW, Network, Thumb Drive 2 SATA (No capacity limit ; 4TB of more)	
The Number of HDD Others Power Consumption		60W	
others	Power Consumption Operating Temperature	5 ~40°C(41~104°F)	
	Relative Humidity	5 ~40 C(41~104 F) Maximum 80% non-condensing	
	Dimension	13.39(W)×9.84(D)×2.36(H)inches /	
		340(W)×250(D)×60(H)mm	

1. Cellular data service required. Software may not compatible due to OS version requirements